Mixed-Use Zones 23-4D-4070

## 23-4D-4070 Mixed-Use 1B (MU1B) Zone

(A) Purpose. Mixed-use 1B (MU1B) zone is intended to allow housing, office or service employment, and retail and entertainment within walking distance of low intensity residential neighborhoods, or to maintain an area with an existing pattern of commercial uses in house-scale buildings.

- (B) **Overview.** This zone allows residential, office, and a broad array of commercial uses in detached house scale buildings. It can be summarized as:
  - (1) eligible for affordable housing bonus programs; and
  - (2) the compatibility effects of this zone may require additional setbacks but do not require height stepbacks.
- (C) **Requirements.** A lot zoned mixed-use 1B shall comply with the requirements of this subsection, which are established in the following tables:
  - (1) Table (A) (Lot Size and Intensity);
  - (2) Table (B) (Building Placement);
  - (3) Table (C) (Building Form);
  - (4) Table (D) (Height);
  - (5) Table (E) (Encroachments);
  - (6) Table (F) (Parking);
  - (7) Table (G) (Frontages);
  - (8) Table (H) (Impervious Cover); and
  - (9) Table (I) (Open Space).



Table 23-4D-4070(A) Lot Size and Intensity							
	Lot				Building		
	Principal Dwellin (ma				Size (ma)	c.)	
Allowed Use	Base Standard	AHBP Bonus <sup>1</sup>	Width (min.)	Area (min.)	Base Standard The less restrictive shall apply between:	AHBP Bonus <sup>1</sup>	
Single-Family	8	+0	40'	5,000 sf	0.4 FAR or 2,300 sf	+0 FAR	
Single-Family Attached	18	+0	25'	2,500 sf	0.4 FAR or 1,150 sf	+0 FAR	
Duplex	18	+0	50'	5,000 sf	0.4 FAR or 2,300 sf	+0 FAR	
Cottage Court	24	+0	50'	5,000 sf	0.6 FAR	+0 FAR	
Multi-Family	24	+12	50'	5,000 sf	0.4 FAR or 2,300 sf	+0.6 FAR	
Townhouse	24	+0	18'	1,800 sf	0.4 FAR or 1,500 sf	+0 FAR	
Other Allowed Uses	_	+0	50'	5,000 sf	1 FAR	+0 FAR	
Accessory Allowed Use		Lot Size			Size (max.)		
Accessory Dwelling Unit		3,500 to 4,99	99 sf	9 sf 750 sf			
Accessory Dwelling Unit		5,000 to 6,99	99 sf	9 sf 975 sf			
Accessory Dwelling Unit	7	7,000 sf or gre	eater	ater 1,100 sf			

Only one Accessory Dwelling Unit may be built and does not count towards principal Units per Acre limit.


Preservation Incentive: Accessory Dwelling Unit does not count toward FAR limit when existing house (at least 10

years old) is preserved.


Accessory Dwelling Unit size counts towards the principal use's FAR limit.

<sup>&</sup>lt;sup>1</sup> To receive affordable housing bonus, a project must comply with Article 23-3E (Affordable Housing).

## **Building Placement Diagram**



## **Building Form Diagram**



**Key for Diagrams** 

---- ROW / Lot Line
Buildable Area

Building Setback Lin	ie
----------------------	----

Building Footprint

Table	23-4D-407	O(B) Build	ding Place	ment

(1) Setback (Distance from	Front	Side St.	Side	Rear
ROW / Lot Line)	A	B	C	D
Minimum	25'	15'	5'	5'

Front and side street setback exceptions are provided in Section 23-4E-7070 (Setback Exceptions)

## (2) Additional Setback

Where street right-of-way, public easement, or utilities easement is required, additional setback and/or easement shall be provided.

## (3) Compatibility Setback

(a) Where a portion of a building is across an alley less than 20 feet in width from a property zoned Residential House-Scale; or is adjacent to a property zoned Residential House-Scale. Then minimum setbacks shall be provided along the alley or shared lot line that comply with subsections (b) and (c).

(b) Compatibility Setback		Side		
	Front	St.	Side	Rear
	A	B	C	D
For lots ≤ 75′ wide	25'	15′	15′	30'
For lots > 75' wide	25′	15′	20'	30'

(c) Where a compatibility setback is required along a side or rear lot line, then a landscape buffer shall be provided that complies with Section 23-4E-4090 (Intermittent Visual Obstruction Buffer).

## Table 23-4D-4070(C) Building Form (1) Overall Building Envelope Width (max.) 60'

(2) Building Articulation on Additions and New Construction

Articulation is required for three facades of a building.

(3) Facades, All Stories

(-)		
Facade Length without Articulation (max.)	36'	•
Articulation Length (min.)	10'	G
Articulation Depth (min.)	4'	<b>G</b>


**Key for Diagrams** 

# Building Height Diagram 1

---- ROW / Lot Line

--- Building Setback Line

## **Encroachments Diagram**



Encroachment

Table 23-4D-4070(D) Height		
(1) Primary and Accessory Buildi	ngs	
To Top Plate (max.)	22'	1
Overall (max.)	32'	0
(2) Accessory Structure		
Overall (max.)	12'	

Table 23-4D-4070(E) Encroachments							
	Front	Side St.	Side	Rear			
(1) Encroachment Type	(max.)	(max.)	` _ ′	(max.)			
	The state of the s	G	W	N			
Private Frontage	10'	10'	_				
Steps and/or ramps to							
<b>Building Entrance</b>	5'	5'	_	_			
Architectural Features	3'	3'	3'	3'			
Porch, Stoop, or		5'					
Uncovered Steps <sup>1</sup>		5					

Ramp. When a ramp encroaches into a setback, then the ramp shall comply with Section 23-4E-7080 (Standards for Ramps Located Within Encroachments).


Landscaping may be located in a required setback.

Encroachments within a right-of-way, public easement, or utility easement require a license agreement or encroachment agreement.

## (2) Height Encroachments

See Section 23-4E-7050 (Encroachments Above Maximum Height) for additional standards.

<sup>&</sup>lt;sup>1</sup>3' max above ground.



**Key for Diagrams** 

---- ROW / Lot Line

--- Building Setback Line

Parking Area

## Table 23-4D-4070(F) Parking

## (1) Parking Requirements

See Section 23-4D-4040 (Parking Requirements) for standards.

(2) Setback	Front	Side St.	Side Q	Rear R
At-Grade and				
Above-Grade	30' <sup>1</sup>	20'	2'	5'
Below-Grade	25'	15'	5'	5'

(3) Parking Driveway		
Width	10' max.	S

Driveways may be shared between adjacent parcels. When lot has adjacent alley with a right-of-way width of 20' or greater, parking must be accessed only from the alley.

Garage doors along the front facade of the primary building must occupy no more than one-third the width of the front facade.

Table 23-4D-4070(G) Frontages						
(1) Private Frontage Type	Front	Side St.	Standards			
Porch: Projecting	Α	Α	23-4E-1040			
Porch: Engaged	Α	Α	23-4E-1050			
Stoop	Α	Α	23-4E-1060			

For non-residential uses, loading docks, overhead doors, and other service entries must be screened and not be located on primary street facades.

### (2) Pedestrian Access

All units must have pedestrian access from the primary street, or for corner lots, from the primary street or side street.

**Key for Tables** 

A = Allowed

— = Not Allowed

N/R = No Requirement

<sup>&</sup>lt;sup>1</sup> Required parking space(s) must not be located in front of the front facade of the building.

Table 23-4D-4070(H) Impervious Cover							
(1) Impervious Cover	% (max.)	Standards					
Impervious Cover	70% <sup>2</sup>	23-3D-3					
Building Cover	50%						
See Division 23-3D-3 (Impervious Cover) for additional							
standards.							

<sup>&</sup>lt;sup>2</sup>The maximum impervious cover may not be attainable due to unique site characteristics, such as trees, waterways, and steep slopes. Where necessary, the project must reduce the impervious cover to

comply with other requirements of this Title.

Table 23-4D-4070(I) Open Space			
(1) Open Space Type	Area per Unit (min.)		
Personal <sup>3</sup>	100 sf		
(2) Area Requirements	Width	Depth	Area
	(min.)	(min.)	(min.)
Ground level	10'	10'	100 sf
Above ground	5'	5'	50 sf

Personal open space requirement may be met by ground floor personal open space, upper story balcony, or roof deck

Personal open space requirements must not be met by open space provided in required front or side street setbacks.

<sup>&</sup>lt;sup>3</sup> The Cottage Court Use has additional open space standards. See Section 23-4E-6160 (Cottage Court).